

Split Air Conditioner

Umi series

TOYOTOMI

FEATURES



SPECIFICATIONS

MODEL		INDOOR	UTN-09AP	UTN-12AP	UTN-17AP	UTN-21AP
		OUTDOOR	UTG-09AP	UTG-12AP	UTG-17AP	UTG-21AP
COOLING CAPACITY			9,212 BTU (2.70 kW)	10,918 BTU (3.20 kW)	15,695 BTU (4.60 kW)	21,154 BTU (6.20 kW)
HEATING CAPACITY			9,554 BTU (2.80 kW)	11,601 BTU (3.40 kW)	17,742 BTU (5.20 kW)	22,178 BTU (6.50 kW)
COOLING	SEER		6.6	6.5	6.4	6.8
	COOLING ENERGY CLASS		A++	A++	A++	A++
HEATING	SCOP AVERAGE ZONE		4.2	4.1	4.0	4.0
	ENERGY CLASS AVERAGE ZONE		A+	A+	A+	A+
	SCOP WARMER ZONE		5.2	5.1	5.1	5.1
	ENERGY CLASS WARMER ZONE		A+++	A+++	A+++	A+++
POWER SOURCE			220-240V, 50Hz			
DEHUMIDIFYING CAPACITY			1.4 L / h	1.4 L / h	1.8 L / h	1.8 L / h
COMPRESSOR			Rotary			
REFRIGERANT			R32			
DIMENSIONS (W x H x D)	INDOOR		817x308x251	897x341x268	1017x366x289	1127x397x324
	OUTDOOR		789x390x600	789x390x600	791x373x590	948x428x591
WEIGHT	INDOOR		10.0	12.5	16.0	19.5
	OUTDOOR		27.5	27.5	29.0	39.5
FEATURES			Intelligent preheating, Intelligent defrost, Self clean function, Energy saving function, Anti-corrosion protection, 8°C heating			

TOYOTOMI CO., LTD.

5-17, Momozono-cho,
Mizuho-ku, Nagoya
467-0855 JAPAN
TEL: +81-52-822-1108
FAX: +81-52-824-7151
E-mail: ftd@toyotomi.jp
Website: www.toyotomi.jp

#TB230142 New: 09/23

Subject to change with or without notice